



CONNECTIONS		G60	D	DS
CL	Control Line	Male ½ BSP 60°cone	Male M22x1,5 DIN 3861L (Tube D.15)	Male M22x1,5 DIN 3861L (Tube D.15)
SL	Supplementary Line	Male ¼ BSP 60°cone	Male M16x1,5 DIN 3861L (Tube D.10)	Male M16x1,5 DIN 3861L (Tube D.10)
RL	Return line	Maschio ¼ BSP 60°cone	Male M14x1,5 DIN 3861L (Tube D.8)	Male M14x1,5 DIN 3861L (Tube D.8)

LIMITS OF USE	
Max pressure CL port	150 bar
Max pressure SL, RL port	35 bar
Hydraulic fluid	Hydraulic oil DIN 51524
Viscosity range	10/380 cSt
Filtration range	NAS 1638 class 9
Temperature	-20/+90 °C

Key features and operating instructions:

- Safe and easy connection of trailer brake system to tractor
- If CL coupling is not connected, the SL coupling cannot be connected
- Connection sequence: first CL coupling, then SL coupling
- Safe and easy manual disconnection: pull the operation plate
- Automatic breakaway disconnection when cable pulled by the trailer
- Swivelling male fittings in order to eliminate hoses tension

ORDER PART NUMBER

20 / **5873** / **xx**

G60: 60° BSP connecting system
D: 24° DIN 3861L connecting system
DS: 24° DIN 3861L connecting system and female coupling ISO 5676 for Spring combined cylinders with equivalent areas

5873: Dual Line Coupling

20: Product class

